

**Premium Acoustic POD Designed**  
**SOLO, DUAL, QUAD, HEXA**



**PREMIUM ACOUSTIC POD DESIGNED FOR LARGE TEAM  
MEETINGS, COLLABORATIVE WORKSHOPS, AND  
BRAINSTORMING SESSIONS.**

[www.dminteract.com](http://www.dminteract.com)



[info@dminteract.com](mailto:info@dminteract.com)



801 Dundas Street East, Unit #D6, Mississauga



Ontario, L4Y 4G9



## PRODUCT SPECIFICATIONS

|                               |                                                                                                                                                                                                                                                                         |                                                                                     |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Brand Name:</b>            |                                                                                                                                                                                       |                                                                                     |
| <b>Model Number</b>           | DM-SoloPod                                                                                                                                                                                                                                                              |  |
| <b>Person Capacity</b>        | Single Person                                                                                                                                                                                                                                                           |                                                                                     |
| <b>Color Option</b>           | Light Gray, Black & Green                                                                                                                                                                                                                                               |                                                                                     |
| <b>Connectivity</b>           | Standard 100-240 V / 50-60 Hz power supply   Also mentions a 12 V USB power supply for the booth.                                                                                                                                                                       |                                                                                     |
| <b>Lighting</b>               | 4000K LED light, luminaire efficiency: 80-90 lm/w, 19W flat panel light                                                                                                                                                                                                 |                                                                                     |
| <b>Privacy</b>                | Advanced sound insulation                                                                                                                                                                                                                                               |                                                                                     |
| <b>Air Quality</b>            | Turbo Fan + PD long-path sound insulation air circulation pipeline. Adopting a manually adjustable wind speed turbine fresh air system, with adjustable speed: 0-1500/RPM, maximum ventilation: 320m <sup>3</sup> /h. The air in the booth can be completely circulated |                                                                                     |
| <b>Smart Management</b>       | Motion sensor and switch control for lighting and fan                                                                                                                                                                                                                   |                                                                                     |
| <b>Integration</b>            | 5-hole socket * 1, two-position switch * 1                                                                                                                                                                                                                              |                                                                                     |
| <b>Back Wall Options</b>      | Not specified                                                                                                                                                                                                                                                           |                                                                                     |
| <b>Eco-Friendly Materials</b> | 38 mm double-layer Carbon crystal panel module + 2 mm high polymer damping sound insulation material                                                                                                                                                                    |                                                                                     |
| <b>Dimensions</b>             | External size: W 988 mm × D 1010 mm × H 2288 mm.<br>Internal size: W 856 mm × D 900 mm × H 2156 mm.                                                                                                                                                                     |                                                                                     |



## PRODUCT SPECIFICATIONS

|                               |                                                                                                                                                                                                                                                                         |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Brand Name:</b>            | DMInteract®<br>FROM VISUALIZATION TO COLLABORATION                                                                                                                                                                                                                      |
| <b>Model Number</b>           | DM-DualPod                                                                                                                                                                           |
| <b>Person Capacity</b>        | Two Persons                                                                                                                                                                                                                                                             |
| <b>Color Option</b>           | Light Gray, Black & Green                                                                                                                                                                                                                                               |
| <b>Connectivity</b>           | Standard 100-240 V / 50-60 Hz power supply   Also mentions a 12 V USB power supply for the booth.                                                                                                                                                                       |
| <b>Lighting</b>               | 4000K LED light, luminaire efficiency: 80-90 lm/w, 19W flat panel light                                                                                                                                                                                                 |
| <b>Privacy</b>                | Advanced sound insulation                                                                                                                                                                                                                                               |
| <b>Air Quality</b>            | Turbo Fan + PD long-path sound insulation air circulation pipeline. Adopting a manually adjustable wind speed turbine fresh air system, with adjustable speed: 0-1500/RPM, maximum ventilation: 320m <sup>3</sup> /h. The air in the booth can be completely circulated |
| <b>Smart Management</b>       | Motion sensor and switch control for lighting and fan                                                                                                                                                                                                                   |
| <b>Integration</b>            | 5-hole socket * 1, two-position switch * 1                                                                                                                                                                                                                              |
| <b>Back Wall Options</b>      | Not specified                                                                                                                                                                                                                                                           |
| <b>Eco-Friendly Materials</b> | 38 mm double-layer Carbon crystal panel module + 2 mm high polymer damping sound insulation material                                                                                                                                                                    |
| <b>Dimensions</b>             | External size: W 1488 mm × D 1250 mm × H 2288 mm.<br>Internal size: W 1356 mm × D 1140 mm × H 2156 mm.                                                                                                                                                                  |



## PRODUCT SPECIFICATIONS

|                               |                                                                                                                                                                                                                                                                         |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Brand Name:</b>            | <b>DMInteract®</b><br>FROM VISUALIZATION TO COLLABORATION                                                                                                                                                                                                               |
| <b>Model Number</b>           | DM-QuadPod                                                                                                                                                                           |
| <b>Person Capacity</b>        | Four Persons                                                                                                                                                                                                                                                            |
| <b>Color Option</b>           | Light Gray, Black & Green                                                                                                                                                                                                                                               |
| <b>Connectivity</b>           | Standard 100-240 V / 50-60 Hz power supply   Also mentions a 12 V USB power supply for the booth.                                                                                                                                                                       |
| <b>Lighting</b>               | 4000K LED light, luminaire efficiency: 80-90 lm/w, 19W flat panel light                                                                                                                                                                                                 |
| <b>Privacy</b>                | Advanced sound insulation                                                                                                                                                                                                                                               |
| <b>Air Quality</b>            | Turbo Fan + PD long-path sound insulation air circulation pipeline. Adopting a manually adjustable wind speed turbine fresh air system, with adjustable speed: 0-1500/RPM, maximum ventilation: 320m <sup>3</sup> /h. The air in the booth can be completely circulated |
| <b>Smart Management</b>       | Motion sensor and switch control for lighting and fan                                                                                                                                                                                                                   |
| <b>Integration</b>            | 5-hole socket * 1, two-position switch * 1                                                                                                                                                                                                                              |
| <b>Back Wall Options</b>      | Not specified                                                                                                                                                                                                                                                           |
| <b>Eco-Friendly Materials</b> | 38 mm double-layer Carbon crystal panel module + 2 mm high polymer damping sound insulation material                                                                                                                                                                    |
| <b>Dimensions</b>             | External size: W 2188 mm × D 1610 mm × H 2288 mm.<br>Internal size: W 2056 mm × D 1500 mm × H 2156 mm.                                                                                                                                                                  |



### PRODUCT SPECIFICATIONS

|                        |                                                                                                                                                                                                                                                                         |                                                                               |  |  |  |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|--|--|--|
| Brand Name:            | <div>DMInteract<sup>®</sup></div> <div>FROM VISULIZATION TO COLLABORATION</div>                                                                                                                                                                                         |                                                                               |  |  |  |
| Model Number           | DM-HexaPod                                                                                                                                                                                                                                                              | <div><div></div><div></div><div></div><div></div><div></div><div></div></div> |  |  |  |
| Person Capacity        | Six Persons                                                                                                                                                                                                                                                             |                                                                               |  |  |  |
| Color Option           | Light Gray, Black & Green                                                                                                                                                                                                                                               |                                                                               |  |  |  |
| Connectivity           | Standard 100-240 V / 50-60 Hz power supply   Also mentions a 12 V USB power supply for the booth.                                                                                                                                                                       |                                                                               |  |  |  |
| Lighting               | 4000K LED light, luminaire efficiency: 80-90 lm/w, 19W flat panel light                                                                                                                                                                                                 |                                                                               |  |  |  |
| Privacy                | Advanced sound insulation                                                                                                                                                                                                                                               |                                                                               |  |  |  |
| Air Quality            | Turbo Fan + PD long-path sound insulation air circulation pipeline. Adopting a manually adjustable wind speed turbine fresh air system, with adjustable speed: 0-1500/RPM, maximum ventilation: 320m <sup>3</sup> /h. The air in the booth can be completely circulated |                                                                               |  |  |  |
| Smart Management       | Motion sensor and switch control for lighting and fan                                                                                                                                                                                                                   |                                                                               |  |  |  |
| Integration            | 5-hole socket * 1, two-position switch * 1                                                                                                                                                                                                                              |                                                                               |  |  |  |
| Back Wall Options      | Not specified                                                                                                                                                                                                                                                           |                                                                               |  |  |  |
| Eco-Friendly Materials | 38 mm double-layer Carbon crystal panel module + 2 mm high polymer damping sound insulation material                                                                                                                                                                    |                                                                               |  |  |  |
| Dimensions             | External size: W 2188 mm × D 1610 mm × H 2288 mm.<br>Internal size: W 2056 mm × D 1500 mm × H 2156 mm.                                                                                                                                                                  |                                                                               |  |  |  |



# ORDER NOW



## CONTACT US



**DEALER ADDRESS:**

Showroom G-02, IT Plaza, Dubai Silicon Oasis, Dubai, United Arab Emirates



**CANADA OFFICE:**

DMInteract Inc 801 Dundas Street East, Unit #D6, Mississauga, Ontario, L4Y 4G9



**CONTACT NUMBER:**

+971-4-3360300 - (Dubai Office)  
437-880-7712 - (Mississauga Office)



**EMAIL ADDRESS:**

info@dminteract.com